


#### **BUBBLE FREE - WATERPROOF - ANTI TERMITE**

Heatproof superior wood adhesive with Cross Linking Polymer Technology Conforms to European D3 Standard (BS:EN 204:205).

#### **GREEN PRODUCT VOC FREE**

# **Application Areas**

- ★ Solid Wood to Wood
- ★ Postforming of Laminate
- ★ Laminate to Plywood & MDF
- ★ Veeneer to Plywood & MDF
- ★ Skin Moulded Doors Solid Wood Doors & Solid Wood Furniture
- ★ Finger Jointing of Solid Wood Panels



#### **Features**

Appearance	White Viscous Liquid
Solid Contents (%)	50% ± 2%
PH Value	2.5 - 4.5
Viscosity in Poise	200 - 300
Coverage	68 - 76 sq.ft. per kg
Setting Time	2 - 8 hr

## **Benefits**

- ★ Cross Linking Polymer provides excellent water and heat resistance.
- ★ Superior bonding Strength.
- ★ Extra Coverage with high spreadability.
- ★ Suitable for high moisture environment like kitchens and bathrooms.
- ★ Long lasting & High Durability thus economical.

# **Pack Sizes**

250gm, 500gm, 1kg, 2kg, 5kg, 10kg, 20kg, 50kg, 1kgPP

**Shelf Life** - 12 months

## **Storage**

Store in a clean place temperature 1°C to 30°C away from direct sunlight